

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX
Revision date : 08-07-2015
Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

VVT Power WC - WC 5000
Carton 4x5 liter LX (507-0003-003)

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Washing and cleaning products (including solvent based products)

Uses advised against

This product should not be used for purposes other than the applications referred to above.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

"Viss visapkārt tīrs", SIA

Street : Ganību dambis 7 a

Postal code/city : LV-1045 Rīga

Telephone : +371 67566306

Telefax : +371 67566305

Information contact : Mr. Egils Ozolins

Website : www.vvt.eu

E-mail (competent person) : info@vvt.eu

1.4 Emergency telephone number

National Poisons Information Service (NPIS) Email: director.birmingham.unit@npis.org Website: <http://www.npis.org/>

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Eye Dam. 1 ; H318 - Serious eye damage/eye irritation : Category 1 ; Causes serious eye damage.

Skin Corr. 1A ; H314 - Skin corrosion/irritation : Category 1A ; Causes severe skin burns and eye damage.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Corrosion (GHS05)

Signal word

Danger

Hazard components for labelling

ALCOHOLS, C9-11, ETHOXYLATE ; CAS No. : 68439-46-3

Hazard statements

H314 Causes severe skin burns and eye damage.

Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX

Revision date : 08-07-2015

Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P310	Immediately call a POISON CENTER/doctor/....
P321	Specific treatment (see ... on this label).
P301+P330+P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405	Store locked up.

2.3 Other hazards

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

2.4 Additional information

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Hazardous ingredients

PHOSPHORIC ACID ; REACH registration No. : 01-2119485924-24 ; EC No. : 231-633-2; CAS No. : 7664-38-2

Weight fraction : $\geq 5 - < 10 \%$

Classification 1272/2008 [CLP] : Skin Corr. 1B ; H314 Eye Dam. 1 ; H318

SULPHURIC ACID ; REACH registration No. : 01-21194258838-20 ; EC No. : 231-639-5; CAS No. : 7664-93-9

Weight fraction : $\geq 2,5 - < 5 \%$

Classification 1272/2008 [CLP] : Skin Corr. 1A ; H314 Eye Dam. 1 ; H318

CITROENZUURMONOHYDRAAT ; REACH registration No. : 01-2119457026-42 ; EC No. : 201-069-1; CAS No. : 5949-29-1

Weight fraction : $\geq 2,5 - < 10 \%$

Classification 1272/2008 [CLP] : Eye Irrit. 2 ; H319

ALCOHOLS, C9-11, ETHOXYLATE ; REACH registration No. : 01-2119980051-45 ; CAS No. : 68439-46-3

Weight fraction : $\geq 1 - < 2,5 \%$

Classification 1272/2008 [CLP] : Eye Dam. 1 ; H318

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

No special measures are necessary.

In case of skin contact

Wash immediately with: Water and soap Change contaminated, saturated clothing. Wash contaminated clothing prior to re-use.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Call a physician in any case! Do NOT induce vomiting. If major quantity of dust is swallowed or inhaled, immediately

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX

Revision date : 08-07-2015

Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

drink: Water

4.2 Most important symptoms and effects, both acute and delayed

The following symptoms may occur: No known symptoms to date. Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

None

SECTION 5: Firefighting measures

5.1 Extinguishing media

None

5.2 Special hazards arising from the substance or mixture

None

5.3 Advice for firefighters

None

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Protective equipment

Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Emergency procedures

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Make sure spills can be contained, e.g. in sump pallets or kerbed areas. In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

For containment

Collect in closed and suitable containers for disposal. Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Suitable material for taking up: Sand Absorbing material, organic

6.4 Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage



7.1 Precautions for safe handling

None

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX

Revision date : 08-07-2015

Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

Keep/Store only in original container. Suitable container/equipment material: Stainless steel Polyethylene (PE)
Unsuitable container/equipment material: Butyl caoutchouc (butyl rubber)

Hints on joint storage

Storage class : 12

Storage class (TRGS 510) : 8B

7.3 Specific end use(s)

None

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

PHOSPHORIC ACID ; CAS No. : 7664-38-2

Limit value type (country of origin) : TRGS 900 (D)

Parameter : E: inhalable fraction

Limit value : 2 mg/m³

Peak limitation : 2(I)

Remark : Y

Version : 02-04-2014

Limit value type (country of origin) : STEL (EC)

Limit value : 2 mg/m³

Version : 08-06-2000

Limit value type (country of origin) : TWA (EC)

Limit value : 1 mg/m³

Version : 08-06-2000

SULPHURIC ACID ; CAS No. : 7664-93-9

Limit value type (country of origin) : TRGS 900 (D)

Parameter : E: inhalable fraction

Limit value : 0,1 mg/m³

Peak limitation : 1(I)

Remark : Y

Version : 02-04-2014

Limit value type (country of origin) : TWA (EC)

Parameter : E: inhalable fraction

Limit value : 0,05 mg/m³

Version : 17-12-2009

8.2 Exposure controls

Personal protection equipment



Eye/face protection

Eye glasses with side protection

Skin protection

Hand protection Suitable gloves type DIN EN 374 Butyl caoutchouc (butyl rubber) NBR (Nitrile rubber) Required properties liquid-tight. Breakthrough time (maximum wearing time) : > 480 min Thickness of the glove material Nitril: 0,12 mm Butyl: 0,50 mm

General health and safety measures

Immediately remove any contaminated clothing, shoes or stockings. Wash contaminated clothing prior to re-use.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX
Revision date : 08-07-2015
Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

Environmental exposure controls

See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour : red

Odour : Perfume

Safety relevant basis data

Physical state :			liquid
Melting point/melting range :			No data available
Initial boiling point and boiling range :	(1013 hPa)	>	100 °C
Decomposition temperature :		>	200 °C
Freezing point :			No data available
Flash point :			not applicable
Auto-ignition temperature :			not applicable
Lower explosion limit :			not applicable
Upper explosion limit :			not applicable
Vapour Pressure :	(20 °C)		No data available
Evaporation rate (n-butylacetate = 1) :			No data available
Density :	(20 °C)	ca.	1,09 g/cm ³
Water solubility :	(20 °C)		100 Wt %
pH :		<	1
Partition coefficient (n-octanol/water) :		<	3
Viscosity :	(20 °C)	ca.	700 mPa.s
Vapour density (air = 1) :	(101 kPa)		No data available

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

not applicable

10.2 Chemical stability

Stable under normal conditions of use

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Strong oxidizers

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX

Revision date : 08-07-2015

Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

Acute oral toxicity

Parameter : LD50 (PHOSPHORIC ACID ; CAS No. : 7664-38-2)
Exposure route : Oral
Species : Rat
Effective dose : 1530 mg/kg

Acute dermal toxicity

Parameter : LD50 (PHOSPHORIC ACID ; CAS No. : 7664-38-2)
Exposure route : Dermal
Species : Rabbit
Effective dose : 2740 mg/kg

Irritant and corrosive effects

Primary irritation to the skin

Irritant.

Irritation to eyes

Irritant.

Irritation to respiratory tract

No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Germ cell mutagenicity

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

STOT-single exposure

not applicable

STOT-repeated exposure

Prolonged or repeated contact with skin or mucous membrane result in irritation symptoms such as redness, blistering, dermatitis, etc.

SECTION 12: Ecological information

12.1 Toxicity

Harmless to aquatic organisms up to the tested concentration

12.2 Persistence and degradability

Biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Other adverse effects

None

12.7 Additional ecotoxicological information

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX

Revision date : 08-07-2015

Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

Delivery to an approved waste disposal company. Contaminated packages must be completely emptied and can be re-used following proper cleaning. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number

No information available.

14.2 UN proper shipping name

No information available.

14.3 Transport hazard class(es)

No information available.

14.4 Packing group

No information available.

14.5 Environmental hazards

No information available.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

non-ionic surfactants	< 5	%
perfumes	< 5	%
Benzyl alcohol	< 5	%
Alpha-isomethyl ionone	< 5	%

National regulations

Water hazard class (WGK)

Class : 1 (Slightly hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

Betriebssicherheitsverordnung (BetrSichV)

No flammable liquid according to BetrSichV.

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

02. Labelling according to Regulation (EC) No. 1272/2008 [CLP]

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road
ASTM = American Society of Testing and Materials (US)
CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)
DNEL = Derived No-Effect Level
DT50 = Time for 50% loss; half-life

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : VVT Power WC - WC 5000
Carton 4x5 liter LX

Revision date : 08-07-2015

Print date : 21-01-2016

Version (Revision) : 3.1.0 (3.0.1)

EbC50 = Median effective concentration (biomass, e.g. of algae)
EC50 = Median effective concentration
EINECS = European Inventory of Existing Commercial Chemical Substances
ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)
ErC50 = Median effective concentration (growth rate, e.g. of algae)
EWC = European Waste Catalogue
IATA = International Air Transport Association
IC50 = Concentration that produces 50% inhibition
IMDG = International Maritime Dangerous Goods Code
IMO = International Maritime Organization
LC50 = Concentration required to kill 50% of test organisms
LD50 = Dose required to kill 50% of test organisms
LEL = Lower Explosive Limit/Lower Explosion Limit
LOAEL = Lowest observed adverse effect level
MRL = Maximum Residue Limit
NOAEL = No Observed Adverse Effect Level
NOEC = No observed effect concentration
NOEL = No Observable Effect Level
OEL = Occupational Exposure Limits
PBT = Persistent, Bioaccumulative or Toxic
PNEC = Previsible Non Effect Concentration
STEL = Short-Term Exposure Limit
TWA = Time-Weighted Average
vPvB = Very Persistent and Very Bioaccumulative

16.3 Key literature references and sources for data

None

16.4 Classification for mixtures and used evaluation method according to regulation (EC) 1272/2008 [CLP]

No information available.

16.5 Relevant H- and EUH-phrases (Number and full text)

H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.

16.6 Training advice

None

16.7 Additional information

Article No.: 507

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.