

Technical datasheet

Axelle R - 20 I

4003035

APPLICATION

Industrial power cleaner for periodical use.

- Mildly alkaline formula.
- Suited for water- resistant surfaces such as walls, floors, doors and closets.
- Removes greasy marks such as traces of tar, bitumen and rubber.



Axelle R is an ecological light foaming all-purpose cleaner for professional use. Axelle R removes greasy marks, oil stains and traces of tar, bitumen and rubber. Axelle R is extremely suitable for periodic cleaning of water-resistant surfaces such as walls, floors, doors and cupboards. Axelle R cannot be used on rubber, painted surfaces, linoleum, asphalt,... Note: always test first on a sample of the material to be cleaned. Axelle R is free from chlorine compounds, other halogen compounds. All surfactants used in these products are biodegradable. All ingredients of non-mineral origin are fully degradable.

INSTRUCTIONS FOR USE

Manual cleaning: Dose 1-3% in water and clean the surface with a sponge. Allow the solution to work in for 5 to 10 minutes, and then rinse with water. High-pressure cleaning: Prepare a 3% solution in the water tank of the high-pressure spray cleaner. Allow the solution to work in on the surface for 5 to 10 minutes, and then rinse with water.





Technical datasheet

Axelle R - 20 I

4003035





appearance Liquid Colourless to yellow

odeur Odourless viscosity 13,2 cP pH-value 10 relative density 20°C 1,020 Kg/L

LOGISTIC DATA

Product

code 4003035 content 20L

 dimensions
 290 x 252 x 374 mm

 gross weight
 21,29 kg

 net weight
 20,44 kg

 EAN-code
 5407003310030

Pallet

units per pallet 24 layers 2 units per layer 12

dimensions 1200 x 800 x 898 mm gross weight 510,96 kg

