

SAFETY DATA SHEET of: Techno Floor

Revision date: Saturday, April 23, 2016

1 SECTION 1: Identification of the substance/mixture and of the company/undertaking:

1.1 Product identifier:

Techno Floor

1.2	Relevant identified	uses of the	substance or	mixture and	uses advised	against:
	INCICACIII INCIIIIICA	uses of the	Substance of	IIIIALUI E AIIU	uses auviseu	against.

Floor cleaner for professional use

Concentration in use: /

1.3 Details of the supplier of the safety data sheet:

Greenspeed

P.O.Box 1250

2280 CG Rijswijk (ZH), NL

Phone: +31703458737 — Fax: +31703458942

E-mail: greenspeed@greenspeed.eu — Website: http://www.greenspeed.eu/

1.4 Emergency telephone number:

GB: +31 70 345 87 37 // IE: +353 1 809 2166 (public) // NL: +31 30 274 88 88 (Uitsluitend voor professionele hulpverleners)

2 SECTION 2: Hazards identification:

2.1 Classification of the substance or mixture:

Classification of the substance or mixture in accordance with regulation (EU) 1272/2008:

none

2.2 Label elements:		
Pictograms:		
Signal word:		
none		
Hazard statements:		
:	none	
Precautionary statements:		

Contains:

2.3 Other hazards:

none

3 SECTION 3: Composition/information on ingredients:

C8-10 D-glucoside	5% - 15%	CAS number: EINECS: REACH Registration number: CLP Classification:	68515-73-1 500-220-1 01-2119488530-36 H318 Eye Dam. 1
Ethanol	< 5%	CAS number: EINECS: REACH Registration number: CLP Classification:	64-17-5 200-578-6 01-2119457610-43 H225 Flam. Liq. 2 H319 Eye Irrit. 2
D-Glucopyranose, C10-16(even numbered)-alkyl glycosides	< 5%	CAS number: EINECS: REACH Registration number: CLP Classification:	110615-47-9 600-975-8 01-2119489418-23 H315 Skin Irrit. 2 H318 Eye Dam. 1

For the full text of the H & R phrases mentioned in this section, see section 16.

4 SECTION 4: First aid measures:

4.1 Description of first aid measures:

Always ask medical advice as soon as possible should serious or continuous disturbances occur.

Skin contact: rinse with water.

Eye contact: rinse first with plenty of water, if necessary seek medical attention. **Ingestion:** rinse first with plenty of water, if necessary seek medical attention.

Inhalation: in case of serious or continuous discomforts: remove to fresh air and seek medical

attention.

4.2 Most important symptoms and effects, both acute and delayed:

Skin contact: none

Eye contact: redness

Ingestion: diarrhoea, headache, abdominal cramps, sleepiness, vomiting

Inhalation: none

4.3 Indication of any immediate medical attention and special treatment needed:

none

5 SECTION 5: Fire-fighting measures:

5.1 Extinguishing media:

5.2 Special hazards arising from the substance or mixture:

none

5.3 Advice for firefighters:

Extinguishing agents to be avoided:

none

6 SECTION 6: Accidental release measures:

6.1 Personal precautions, protective equipment and emergency procedures:

Do not walk into or touch spilled substances and avoid inhalation of fumes, smoke, dusts and vapours by staying up windRemove any contaminated clothing and used contaminated protective equipment and dispose of it safely.

6.2 Environmental precautions:

do not allow to flow into sewers or open water.

6.3 Methods and material for containment and cleaning up:

Contain released substance, store into suitable containers. If possible remove by using absorbent material.

6.4 Reference to other sections:

for further information check sections 8 & 13.

7 SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

handle with care to avoid spillage.

7.2 Conditions for safe storage, including any incompatibilities:

keep in a sealed container in a closed, frost-free, ventilated room.

7.3 Specific end use(s):

Floor cleaner for professional use

8 SECTION 8: Exposure controls/personal protection:

8.1 Control parameters:

Listing of the hazardous ingredients in section 3, of which the TLV value is known

Ethanol 1,907 mg/m³

8.2 Exposure controls:

Inhalation	respiratory protection is not required. Use ABEK type gas masks in case of irritating exposure. If
protection:	necessary, use with sufficient exhaust ventilation.
protocuom	

Skin protection:	handling with butyl-gloves (EN 374). Breakthrough time: >480' Material thickness: 0,7 mm. Thoroughly check gloves before use. Take of the gloves properly without touching the outside with your bare hands. The manufacturer of the protective gloves has to be consulted about the suitability for a specific work station. Wash and dry your hands.	
Eye protection:	keep an eye-rinse bottle within reach. Tight-fitting safety goggles. Wear a face shield and protective suit in case of exceptional processing problems.	
Other protection:	impermeable clothing. The type of protective equipment depends on the concentration and amount of hazardous substances at the work station in question.	

9 SECTION 9: Physical and chemical properties:

9.1 Information on basic physical and chemical properties:

Melting point/melting range: 0 °C

Boiling point/Boiling range: 78 °C

pH: 6.2

pH 1% diluted in water: /

Vapour pressure/20°C,: 5 850 Pa
Vapour density: not applicable
Relative density, 20°C: 1.013 kg/l
Appearance/20°C: liquid
Flash point: /

Flammability (solid, gas): not applicable

Auto-ignition temperature: 370 $^{\circ}$ C Upper flammability or explosive 19.000 $^{\circ}$

limit, (Vol %):

Lower flammability or explosive 3.000 %

limit, (Vol %):

Explosive properties: not applicable

Oxidising properties: not applicable

Decomposition temperature: /

Solubility in water: completely soluble

Partition coefficient: n- not applicable

octanol/water:

Odour: characteristic
Odour threshold: not applicable

Dynamic viscosity, 20°C: 1 mPa.s

Kinematic viscosity, 20°C: 1 mm²/s

Evaporation rate (n-BuAc = 1): 2.000

9.2 Other information:

Volatile organic component (VOC): 4.00 % Volatile organic component (VOC): 44.297 g/l

10 SECTION 10: Stability and reactivity:

10.1 Reactivity:

stable under normal conditions.

10.2 Chemical stability:

extremely high or low temperatures.

10.3 Possibility of hazardous reactions:

none

10.4 Conditions to avoid:

protect from sunlight and do not expose to temperatures exceeding + 50°C.

10.5 Incompatible materials:

acids, alkalines, oxidants, reductants

10.6 Hazardous decomposition products:

doesn't decompose with normal use

11 SECTION 11: Toxicological information:

11.1 Information on toxicological effects:

About the preparation itself: No additional data available

Calculated acute toxicity, ATE oral: / Calculated acute toxicity, ATE / dermal:

C8-10 D-glucoside	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5,000 mg/kg ≥ 5,000 mg/kg ≥ 50 mg/l
Ethanol	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5,000 mg/kg ≥ 5,000 mg/kg ≥ 50 mg/l
D-Glucopyranose, C10-16(even numbered)-alkyl glycosides	LD50 oral, rat: LD50 dermal, rabbit: LC50, Inhalation, rat, 4h:	≥ 5,000 mg/kg ≥ 5,000 mg/kg ≥ 50 mg/l

12 SECTION 12: Ecological information:

12.1 Toxicity:

C8-10 D-glucoside	LC50 (Fish): EC50 (Daphnia): NOEC (Daphnia): EC50 (Algae):	190 mg/l (96h) (Danio rerio) >100 mg/l (48h) >100 mg/l (72h) 37 mg/l (72 h) (Scenedesmus subspicatus)
Ethanol	LC50 (Fish): EC50 (Daphnia): EC50 (Algae):	13000 mg/L (Oncorhynchus mykiss)(96h) 12340 mg/L (48h) 275 mg/L (Chlorella vulgaris)(72h)

12.2 Persistence and degradability:

The surfactants contained in this preparation comply with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

12.3 Bioaccumulative potential:

	Additional data:
Ethanol	Log Pow: -0,35

12.4 Mobility in soil:

Water hazard class, WGK: 1

Solubility in water: completely soluble

12.5 Results of PBT and vPvB assessment:

No additional data available

12.6 Other adverse effects:

No additional data available

13 SECTION 13: Disposal considerations:

13.1 Waste treatment methods:

The product may be discharged in the indicated percentages of utillization, provided it is neutralised to pH 7. Possible restrictive regulations by local authority should always be adhered to.

14 SECTION 14: Transport information:

14.1 UN number:

not applicable

14.2 UN proper shipping name:

ADR, IMDG, ICAO/IATA not applicable

14.3 Transport hazard class(es):

Class(es): not applicable ldentification number of the hazard:

14.4 Packing group:

not applicable

14.5 Environmental hazards:

not dangerous to the environment

14.6 Special precautions for user:

Hazard characteristics: not applicable
Additional guidance: not applicable

15 SECTION 15: Regulatory information:

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Water hazard class, WGK: 1

Volatile organic component (VOC): 4.000 % Volatile organic component (VOC): 44.297 g/l

Composition by regulation (EC) Nonionic surfactants 5% - 15%, Perfumes

648/2004:

15.2 Chemical Safety Assessment:

No data available

16 SECTION 16: Other information:

Legend to abbreviations used in the safety data sheet:

ADR: The European Agreement concerning the International Carriage of Dangerous

Goods by Road

BCF: Bioconcentration factor

CAS: Chemical Abstracts Service

CLP: Classification, Labelling and Packaging of chemicals

EINECS: European INventory of Existing Commercial chemical Substances

Nr.: number

PTB: persistent, toxic, bioaccumulative

TLV: Threshold Limit Value

vPvB: very persistent and very bioaccumulative substances

WGK: Water hazard class

WGK 1: slightly hazardous for water

WGK 2: hazardous for water

WGK 3: extremely hazardous for water

Legend to the R & H Phrases used in the safety data sheet:

: none H225 Flam. Liq. 2: Highly flammable liquid and vapour. H315 Skin Irrit. 2: Causes skin irritation. H318 Eye Dam. 1: Causes serious eye damage. H319 Eye Irrit. 2: Causes serious eye irritation.

Reason of revision, changes of following items:

not applicable

MSDS reference number:

ECM-108968,00

This safety information sheet has been compiled in accordance with annex II/A of the regulation (EU) No 2015/830. Classification has been calculated in accordance with European regulation 1272/2008 with their respective amendments. It has been compiled with the utmost care. We cannot, however, accept responsibility for damage, of any kind, that may be caused by using these data or the product concerned. To use this preparation for an experiment or a new application, the user must carry out a material suitability and safety study himself.