according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date: 22-12-2020

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Americol Antol 80

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses

Degreaser

Sectors of use [SU]

Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Process categories [PROC]

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 11 - Non industrial spraying

PROC 19 - Manual activities involving hand contact

Environmental release categories [ERC]

ERC 8a - Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

Uses advised against

This product should not be used for purposes other than the applications referred to above.

1.3 Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor)

Americol BV

Street: Sluispolderweg 33

Postal code/city: 1505 HJ Zaandam **Telephone:** +31 (0)75-631 32 44

Information contact: Dept. Safety, Health and Environment

Website: www.americol.nl

E-mail (competent person): info@americol.nl

1.4 Emergency telephone number

National Poisons Information Service (NPIS) Email: director.birmingham.unit@npis.org Website: http://www.npis.org/

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Asp. Tox. 1; H304 - Aspiration hazard: Category 1; May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP] Hazard pictograms



Health hazard (GHS08)

Signal word

Danger

Hazard components for labelling

Page: 1 / 10

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 22-12-2020

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSINE - UNSPECIFIED; CAS No.: 64742-47-8

Hazard statements

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/....

P331 Do NOT induce vomiting.

P405 Store locked up.

Remark

The product is classified and labelled according to EC directives or corresponding national laws.

2.3 Other hazards

Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

2.4 Additional information

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous ingredients

DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSINE - UNSPECIFIED; REACH No.: 01-2119456620-43; EC

No.: 265-149-8; CAS No.: 64742-47-8

Weight fraction : \geq 50 %

Classification 1272/2008 [CLP]: Asp. Tox. 1; H304

2-BUTOXYETHANOL; REACH No.: 01-2119475108-36; EC No.: 203-905-0; CAS No.: 111-76-2

Weight fraction : \geq 2,5 - < 10 %

Classification 1272/2008 [CLP]: Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Skin Irrit. 2; H315

Eye Irrit. 2; H319

Additional information

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice.

Following inhalation

No special measures are necessary.

In case of skin contact

Change contaminated, saturated clothing. Wash contaminated clothing prior to re-use.

After eye contact

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Call a physician in any case! Do NOT induce vomiting. If major quantity of dust is swallowed or inhaled, immediately drink: Water

4.2 Most important symptoms and effects, both acute and delayed

The following symptoms may occur: No known symptoms to date.

4.3 Indication of any immediate medical attention and special treatment needed

None

Page: 2 / 10

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 22-12-2020

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water mist Foam Extinguishing powder Carbon dioxide (CO2)

Unsuitable extinguishing media

Full water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide Carbon dioxide (CO2)

5.3 Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Emergency procedures

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Make sure spills can be contained, e.g. in sump pallets or kerbed areas.

6.3 Methods and material for containment and cleaning up

For containment

Collect in closed and suitable containers for disposal. Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Suitable material for taking up: Sand Absorbing material, organic

6.4 Reference to other sections

See protective measures under point 7 and 8.

SECTION 7: Handling and storage



7.1 Precautions for safe handling

None

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep/Store only in original container. Suitable container/equipment material: Stainless steel Polyethylene (PE)

7.3 Specific end use(s)

None

Page: 3 / 10

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 22-12-2020

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

2-BUTOXYETHANOL; CAS No.: 111-76-2

Limit value type (country of origin): STEL (EC)

Limit value: 50 ppm / 246 mg/m³

Remark:

Version: 31-01-2018 Limit value type (country of origin): TWA (EC)

Limit value: 20 ppm / 98 mg/m³

Remark: H
Version: 31-01-2018

Limit value type (country of origin): Exposure Limit (8h) (NL)

 $\begin{array}{ll} \text{Limit value:} & 100 \text{ mg/m}^3 \\ \text{Remark:} & \text{H} \end{array}$

Version: 01-01-2007

Limit value type (country of origin): Exposure Limit (15min) (NL)

 $\begin{array}{ll} \text{Limit value:} & 246 \text{ mg/m}^3 \\ \text{Remark:} & \text{H} \end{array}$

Version: 01-01-2007

DNEL-/PNEC-values

DNEL/DMEL

2-BUTOXYETHANOL; CAS No.: 111-76-2

Limit value type : DNEL Consumer (local)

Exposure route: Inhalation
Exposure frequency: Long-term
Limit value: 147 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route : Dermal
Exposure frequency : Short-term
Limit value : 89 mg/kg
Safety factor : day(s)

Limit value type : DNEL Consumer (systemic)

Exposure route: Inhalation
Exposure frequency: Short-term
Limit value: 426 mg/m³

Limit value type : DNEL Consumer (systemic)

Exposure route: Oral
Exposure frequency: Short-term
Limit value: 26,7 mg/kg
Safety factor: day(s)

Limit value type : DNEL Consumer (systemic)

Exposure route: Dermal
Exposure frequency: Long-term
Limit value: 75 mg/kg
Safety factor: day(s)

Limit value type : DNEL Consumer (systemic)

Exposure route : Inhalation
Exposure frequency : Long-term
Limit value : 59 mg/m³

Limit value type : DNEL Consumer (systemic)

Page: 4 / 10

(EN/NL)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name: Americol Antol 80

Version (Revision): 5.0.0 (4.0.0) Revision date: 19-10-2020

Print date: 22-12-2020

> Exposure route: Oral Exposure frequency: Long-term Limit value : 6,3 mg/kg Safety factor: day(s)

DNEL worker (systemic) Limit value type:

Dermal Exposure route: Exposure frequency: Short-term 89 mg/kg Limit value: Safety factor: day(s)

Limit value type: DNEL worker (systemic)

Exposure route: Inhalation Exposure frequency: Short-term Limit value: 1091 ma/m³

Limit value type: DNEL worker (systemic)

Exposure route: Inhalation Exposure frequency: Long-term Limit value: 98 mg/m³

DNEL worker (systemic) Limit value type:

Exposure route: Dermal Exposure frequency: Long-term Limit value: 125 mg/kg Safety factor: day(s)

2-BUTOXYETHANOL; CAS No.: 111-76-2

Limit value type: PNEC (Aquatic, freshwater) Exposure route: Water (Including sewage plant)

Limit value: 8,8 mg/l

Limit value type: PNEC (Aquatic, marine water) Exposure route : Water (Including sewage plant)

0,88 mg/l Limit value:

Limit value type: PNEC (Sediment, freshwater)

Exposure route:

Limit value: 34,6 mg/kg dw

PNEC (Sediment, marine water) Limit value type :

Exposure route: Soil

3,46 mg/kg dw Limit value: Limit value type: PNEC (Soil) Exposure route: Soil

Limit value: 2,33 mg/kg dw

PNEC (Sewage treatment plant) Limit value type: Exposure route: Water (Including sewage plant)

Limit value: 463 mg/l

8.2 Exposure controls

Personal protection equipment

Skin protection

Hand protection Suitable gloves type EN ISO 374 Butyl caoutchouc (butyl rubber) NBR (Nitrile rubber) Required properties liquid-tight. Breakthrough time (maximum wearing time) Permeation time (maximum wear time) Thickness of the glove material Nitril: 0,12 mm Butyl: 0,50 mm Skin and body protection: normal working clothes.

General information

Immediately remove any contaminated clothing, shoes or stockings. Wash contaminated clothing prior to re-use.

Environmental exposure controls

See section 7. No additional measures necessary.

Page: 5 / 10

(EN/NL)

according to Regulation (EC) No. 1907/2006 (REACH)



°C

Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 22-12-2020

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Colour: red

Odour : characteristic

Safety characteristics

Physical state: Liquid
Melting point/freezing point: not applicable
Initial boiling point and boiling
(1013 hPa) > 100

Parage:

Decomposition temperature:

No data available

Freezing point:

No data available

No data available

Flash point:

80 °C

Auto-ignition temperature:

> 250 °C

Lower explosion limit:

Vol-9

Lower explosion limit :Vol-%Upper explosion limit :Vol-%

Vapour Pressure: (20 °C) No data available
Evaporation rate (n-butylacetate = No data available
1):

Density : (20 °C) approx. 0,8 g/cm³ **Water solubility :** (20 °C) emulsifies

Partition coefficient (noctanol/water):

 Viscosity:
 (20 °C)
 <</td>
 10 mPa*s

 Cinematic viscosity:
 (40 °C)
 <</td>
 10 mm²/s

Vapour density (air = 1): (101 kPa) No data available

Valt onder Detergentia
Verordening (EG) Nr. 648/2004 yes

J/N

9.2 Other information

None

SECTION 10: Stability and reactivity

10.1 Reactivity

not applicable

10.2 Chemical stability

Stable under normal conditions of use

10.3 Possibility of hazardous reactions

No information available.

10.4 Conditions to avoid

No information available.

10.5 Incompatible materials

Strong oxidizers

10.6 Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects Acute toxicity

Page: 6 / 10

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 22-12-2020

Acute oral toxicity

Parameter: LD50 (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSINE -

UNSPECIFIED; CAS No.: 64742-47-8)

Exposure route : Oral Species : Rat

Effective dose: > 5000 mg/m³

Parameter: LD50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)

Exposure route: Oral
Species: Rat
Effective dose: 1480 mg/kg

Acute dermal toxicity

Parameter: LD50 (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSINE -

UNSPECIFIED; CAS No.: 64742-47-8)

Acute inhalation toxicity

Parameter: LC50 (DISTILLATES (PETROLEUM), HYDROTREATED LIGHT / KEROSINE -

UNSPECIFIED; CAS No.: 64742-47-8)

Exposure route: Inhalation (gas)

Species: Rat

Effective dose : $> 5000 \text{ mg/m}^3$ Exposure time : 8 hour(s)

Parameter: LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)

Exposure route: Inhalation
Species: Rat
Effective dose: 500 ppm

Parameter: LC50 (2-BUTOXYETHANOL ; CAS No. : 111-76-2)

Exposure route: Inhalation
Species: Mouse
Effective dose: 700 ppm

Corrosion

Skin corrosion/irritation

Not an irritant.

Serious eye damage/eye irritation

Not an irritant.

Irritation to respiratory tract

No data available

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

Germ cell mutagenicity

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

This substance does not meet the criteria for classification as CMR category 1A or 1B according to CLP.

STOT-single exposure

not applicable

SECTION 12: Ecological information

12.1 Toxicity

harmless to aquatic organisms up to the tested concentration

Page: 7 / 10

(EN/NL)

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 22-12-2020

12.2 Persistence and degradability

Biodegradable.

12.3 Bioaccumulative potential

No indication of bioaccumulation potential.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

None

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Delivery to an approved waste disposal company. Contaminated packages must be completely emptied and can be reused following proper cleaning. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1 UN number

No dangerous good in sense of these transport regulations.

14.2 UN proper shipping name

No dangerous good in sense of these transport regulations.

14.3 Transport hazard class(es)

No dangerous good in sense of these transport regulations.

14.4 Packing group

No dangerous good in sense of these transport regulations.

14.5 Environmental hazards

No dangerous good in sense of these transport regulations.

14.6 Special precautions for user

None

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Authorisations and/or restrictions on use

Restrictions on use

Use restriction according to REACH annex XVII, no.: 3

Other regulations (EU)

Labelling for contents according to regulation (EC) No. 648/2004

aliphatic hydrocarbons >= 30 % non-ionic surfactants < 5 %

Page: 8 / 10

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date: 19-10-2020 **Version (Revision):** 5.0.0 (4.0.0)

Print date : 22-12-2020

15.2 Chemical safety assessment

Chemical safety assessments for substances in this preparation were not carried out.

SECTION 16: Other information

16.1 Indication of changes

01. Sectors of use [SU] · 02. Label elements · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] · 02. Labelling according to Regulation (EC) No. 1272/2008 [CLP] - Hazard components for labelling · 03. Hazardous ingredients · 08. Occupational exposure limit values

16.2 Abbreviations and acronyms

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

ASTM = American Society of Testing and Materials (US)

CAS No = Chemical Abstracts Service Number (see ACS - American Chemical Society)

DNEL = Derived No-Effect Level

DT50 = Time for 50% loss; half-life

EbC50 = Median effective concentration (biomass, e.g. of algae)

EC50 = Median effective concentration

EINECS = European Inventory of Existing Commercial Chemical Substan

ELINCS = European List of Notified (New) Chemicals (see Tab 7, Background - Guide)

ErC50 = Median effective concentration (growth rate, e.g. of algae)

EWC = European Waste Catalogue

IATA = International Air Transport Association

IC50 = Concentration that produces 50% inhibition

IMDG = International Maritime Dangerous Goods Code

IMO = International Maritime Organization

LC50 = Concentration required to kill 50% of test organisms

LD50 = Dose required to kill 50% of test organisms

LEL = Lower Explosive Limit/Lower Explosion Limit

LOAEL = Lowest observed adverse effect level

MRL = Maximum Residue Limit

NOAEL = No Observed Adverse Effect Level

NOEC = No observed effect concentration

NOEL = No Observable Effect Level

OEL = Occupational Exposure Limits

PBT = Persistent, Bioaccumulative or Toxic

PNEC = Previsible Non Effect Concentration

STEL = Short-Term Exposure Limit

TWA = Time-Weighted Average

vPvB = Very Persistent and Very Bioacccumulative

16.3 Key literature references and sources for data

None

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Indeling van de stof of het mengsel: classificatie conform Verordening (EG) Nr. 1272/2008 [CLP] door middel van calculatiemethode via software.

16.5 Relevant H- and EUH-phrases (Number and full text)

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.

H332 Harmful if inhaled.

16.6 Training advice

None

Page: 9 / 10

according to Regulation (EC) No. 1907/2006 (REACH)



Trade name : Americol Antol 80

Revision date : 19-10-2020 **Version (Revision) :** 5.0.0 (4.0.0)

Print date : 22-12-2020

16.7 Additional information

Article No.: 950

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Page: 10 / 10